


# PACO R80



SKU: PACO80 - XX-XX-XX-XX-XX



## DATASHEET



### GENERAL INFORMATION

APPLICATION	Indoor
DIRECTION OF MOUNTING	Ceiling
VISIBLE DIMENSIONS (Ø×L)	Ø80 × 37 mm
MATERIAL	Aluminium
WEIGHT	119gr
IP RATING	IP20
LIFE TIME	50000 hours
ORIGIN	Greece

### ILLUMINANT

LAMP TYPE	LED
BEAM ANGLE	20D
CRI	Ra80
OUTPUT	IP20
OPTICAL EFFICIENCY %	93%
ENERGY EFFICIENCY	A+
CONNECTION TYPE	Parallel
DIMMABLE OPTION	TRIAC

# PACO R80

SKU: **PACO80** - XX-XX-XX-XX-XX

COLOR  
WATTAGE  
VOLTAGE  
CCT  
DIMMABLE

Color	Wattage*	Voltage*	CCT*	Output	Dimmable*
Anodised ( <b>AN</b> )	3W ( <b>3W</b> )	12VDC ( <b>V1</b> )	2700K ( <b>27K</b> )	100 lm/W	Dim TRIAC ( <b>D1</b> )
Black ( <b>BL</b> )		24VDC ( <b>V2</b> )	3000K ( <b>30K</b> )	110 lm/W	No Dim ( <b>_</b> )
White ( <b>WH</b> )	4W ( <b>4W</b> )	230VAC ( <b>V3</b> )	4000K ( <b>40K</b> )	120 lm/W	
RAL colors ( <b>RL</b> )			5000K ( <b>50K</b> )	120 lm/W	
Nickel plating ( <b>NK</b> )					
Patina ( <b>PT</b> )					

\* Υποχρεωτική επιλογή / Mandatory option

Δημιουργία Κωδικού προϊόντος / Product Code generator

**PACO80- color - wattage - voltage - CCT - dimmable**

EXAMPLE:

*PACO80 - BL-3W-V2-30K-D1*

for PACO R80, black, 3W, 24VDC, 3000K, dim TRIAC