

- For the construction of sealed lighting fixtures
- Possibility of sealing in dedicated profiles
- Increased pressure resistance
- Made of PC with increased resistance to weather conditions

### APPLICATION

- LED protection and light diffusion in lighting fixtures


### MOUNTING

- Snapped in a dedicated profile

### ADDITIONAL INFORMATION

- ATTENTION! rigid cover, not intended for bending or deformation
- standard lengths of KLUŚ profiles and covers: 1000 mm (tolerance  $\pm 1.5$  mm) and 2005 mm / 3010 mm (tolerance + 5 mm); for selected covers: 6050 mm, 10050 mm (tolerance + 5 mm)
- when choosing a different length of profiles / covers than available in the standard, you should additionally choose the cutting service at KLUŚ

### TECHNICAL DRAWING



### TECHNICAL SPECIFICATIONS

Material	PMMA
Shape	flat
Maximum length on request	6000 mm
Width	21 mm
High mechanical resistance	yes
UV resistance	yes

Finish	Light transmission	Length	Possibility of obtaining a line of light	Ref
frosted	55 %	1000 mm	yes	B17152F_1
		2005 mm		B17152F_2
		3010 mm		B17152F_3
semi-transparent	92 %	1000 mm	no	B17152T_1
		2005 mm		B17152T_2
		3010 mm		B17152T_3

## RELATED PROFILES > FACADE



**HR-OPTI**  
A01844

## RELATED PROFILES > FOR FLOORS



**HR-MAX**  
A01829

---

## RELATED SYSTEMS > IN-GROUND AND FACADE SYSTEMS



**HR-MAX**  
A01829+A01827+A01828



**HR-OPTI**  
A01844+C28090N00