

Focusing cover LENS0-11-30DEG

Ref. B17112T



- Focusing the light flux
- Limited chromatic aberration at the edges of the cover
- Resistance to weather conditions

APPLICATION

- LED protection and light focusing in lighting fixtures


MOUNTING

- Snapped in a dedicated profile

ADDITIONAL INFORMATION

- standard lengths of KLUŚ profiles and covers: 1000 mm (tolerance ± 1.5 mm) and 2005 mm / 3010 mm (tolerance + 5 mm); for selected covers: 6050 mm, 10050 mm (tolerance + 5 mm)
- when choosing a different length of profiles / covers than available in the standard, you should additionally choose the cutting service at KLUŚ

TECHNICAL DRAWING



TECHNICAL SPECIFICATIONS

Finish	semi-transparent
Material	PC
Shape	flat
Maximum length on request	6000 mm
Light transmission	80 %
Width	12 mm
Height	7.8 mm
Kąt soczewki Min	30°
Focusing light	yes
UV resistance	yes

Length	Ref
1000 mm	B17112T_1
2005 mm	B17112T_2
3010 mm	B17112T_3

RELATED PROFILES > ARCHITECTURAL



KOZMA
A18040



PDS-T
A02057



PDS-UST
A02725

RELATED PROFILES > FOR SCONCES AND WALL LIGHTING



PLAKIN-DUO
A04106A

RELATED PROFILES > UNIVERSAL



45-16
A08504



45-ALU
A04023



PDS-H
A09204



PDS-ZM-PLUS
A02056



PDS-ZMG
A01418




PDS-NK
A01588




PDS-4-PLUS
A01263


RELATED ACCESSORIES > RELATED LED > HIGH EFFICACY




K-HE-0480-HD-24V
K-HEHD-0480-24



K-HE-0960-HD-24
K-HEHD-0960-24




K-HE-1440-HD-24
K-HEHD-1440-24




K-HE-1920-HD-24
K-HEHD-1920-24


RELATED ACCESSORIES > RELATED LED > WHITE MONO




K-1275-24
K-1275-24



K-0480-24
K-0480-24



K-0960-24
K-0960-24



K-1440-24
K-1440-24