



- Recommended for the construction of sealed lighting fixtures

APPLICATION

- LED protection and light diffusion in lighting fixtures

MOUNTING

- to the profile, by pressing

ADDITIONAL INFORMATION

- standard lengths of KLUŚ profiles and covers: 1000 mm (tolerance ± 1.5 mm) and 2005 mm / 3010 mm (tolerance + 5 mm); for selected covers: 6050 mm, 10050 mm (tolerance + 5 mm)
- when choosing a different length of profiles / covers than available in the standard, you should additionally choose the cutting service at KLUŚ

TECHNICAL DRAWING



TECHNICAL SPECIFICATIONS

Material	PC
Shape	flat
Maximum length on request	3000 mm
Width	12.5 mm
UV resistance	yes

Finish	Light transmission	Length	Possibility of obtaining a line of light	Ref
frosted	59 %	1000 mm	yes	B17208F_1
		2005 mm		B17208F_2
		3010 mm		B17208F_3
clear	88 %	1000 mm	no	B17208C_1
		2005 mm		B17208C_2
		3010 mm		B17208C_3

RELATED PROFILES > ARCHITECTURAL



KOZMA
A18040




OPK-4
A00370



PDS-T
A02057



PDS-UST
A02725




POK-US
A01234




POKET
A01179


RELATED PROFILES > FOR MAIN LIGHTING



DES
A18030



MOD-100
A18049




MOD-50
A18047

RELATED PROFILES > FOR SCONCES AND WALL LIGHTING



LIT-L
A18033



OBIT
A04826




PLAKIN-DUO
A04106A

RELATED PROFILES > ILLUMINATION OF COVES AND ARCHITECTURAL NICHES



NISA-KON
A18027



NISA-KRA
A18026



NISA-NI
A18029




POLI
A07176

RELATED PROFILES > STAIRS ILLUMINATION



POR
A06144



STEP
A18042

RELATED PROFILES > UNIVERSAL



45-16
A08504



45-ALU
A04023



KUBIK-45
A07697



MICRO-H
A00599



MICRO-HG
A01419



MICRO-NK
A01587



MICRO-PLUS
A02966



OLEK
A08505



PDS-4-PLUS
A01263



PDS-H
A09204

Cover HS-11

Ref. B17208F, B17208C



PDS-NK
A01588




PDS-ZM-PLUS
A02056



PDS-ZMG
A01418

RELATED SYSTEMS > GENERAL LIGHTING SYSTEMS



MOD-50
18047



PK-4
A18044+A00370