



## APPLICATION

- LED protection and light diffusion in lighting fixtures

## MOUNTING

- Snapped in a dedicated profile

## ADDITIONAL INFORMATION

- standard lengths of KLUŚ profiles and covers: 1000 mm (tolerance  $\pm 1.5$  mm) and 2005 mm / 3010 mm (tolerance + 5 mm); for selected covers: 6050 mm, 10050 mm (tolerance + 5 mm)
- when choosing a different length of profiles / covers than available in the standard, you should additionally choose the cutting service at KLUŚ

## TECHNICAL DRAWING



## TECHNICAL SPECIFICATIONS

Material	PC
Shape	flat
Maximum length on request	10000 mm
Width	12.4 mm

Finish	Light transmission	Length	Ref
frosted	67 %	1000 mm	B17064F_1
		2005 mm	B17064F_2
		3010 mm	B17064F_3
clear	89 %	1000 mm	B17064C_1
		2005 mm	B17064C_2
		3010 mm	B17064C_3

## RELATED PROFILES > ARCHITECTURAL



**KOZMA**  
A18040



**OPK-4**  
A00370




**PDS-T**  
A02057




**PDS-UST**  
A02725


## RELATED PROFILES > FOR MAIN LIGHTING



**DES**  
A18030




**MOD-100**  
A18049




**MOD-50**  
A18047

## RELATED PROFILES > FOR SCONCES AND WALL LIGHTING



**LIT-L**  
A18033



**OBIT**  
A04826



**PLAKIN-DUO**  
A04106A

## RELATED PROFILES > ILLUMINATION OF COVES AND ARCHITECTURAL NICHES



**NISA-KON**  
A18027



**NISA-KRA**  
A18026



**NISA-NI**  
A18029




**POLI**  
A07176

## RELATED PROFILES > STAIRS ILLUMINATION



**POR**  
A06144



**STEP**  
A18042

RELATED PROFILES > UNIVERSAL




**45-16**  
A08504



**45-ALU**  
A04023



**KUBIK-45**  
A07697



**MICRO-H**  
A00599



**MICRO-HG**  
A01419



**MICRO-NK**  
A01587



**MICRO-PLUS**  
A02966



**OLEK**  
A08505



**PDS-4-PLUS**  
A01263




**PDS-H**  
A09204



**PDS-NK**  
A01588




**PDS-ZM-PLUS**  
A02056




**PDS-ZMG**  
A01418

RELATED SYSTEMS > GENERAL LIGHTING SYSTEMS



**MOD-100**  
18049



**MOD-50**  
18047



**PK-4**  
A18044+A00370